

INVERTER Wall Mounted

Simple design with energy saving.



ASYG07/09/12LE



ASYG14LE



Wireless R.C.



For ASYG14LE



For ASYG07/09/12LE

CLASS ALL
A **DC**

ASYG07LE **NEW**

CLASS ALL
A **DC**

ASYG09LE **NEW**

CLASS ALL
A **DC**

ASYG12LE **NEW**

CLASS ALL
A **DC**


ASYG14LE **NEW**

i-PAM (12/14) V-PAM (07/09)

Up/Down Adjust Restart Auto Changeover HEAT 10°C Economy POWERFUL Low noise Sleep Program Filter Ion AF Wash

Compact design

Indoor unit




For ASYG07/09/12LE

Outdoor unit



For AOYG07/09/12LE

High density heat exchanger arrangement




Specifications

Model No.	Indoor unit		ASYG07LE	ASYG09LE	ASYG12LE	ASYG14LE
	Outdoor unit		AOYG07LE	AOYG09LE	AOYG12LE	AOYG14LE
Power Source	V/∅/Hz		230/1/50	230/1/50	230/1/50	230/1/50
Capacity	Cooling	kW	2.1	2.5	3.4	4.0
	Heating		3.0	3.2	4.0	5.0
Input Power	Cooling/Heating	kW	0.47/0.69	0.64/0.75	0.92/0.99	1.11/1.31
EER - Energy Class	Cooling	W/W	4.47-A	3.91-A	3.70-A	3.62-A
COP - Energy Class	Heating		4.38-A	4.27-A	4.04-A	3.83-A
Running Current	Cooling/Heating	A	2.7/3.5	3.5/3.8	4.4/4.7	5.3/6.0
Moisture Removal	l/h		1.3	1.3	1.8	2.1
Noise (Indoor)	Cooling H/M/L/Q	dB(A)	43/38/31/21	43/38/31/21	43/38/31/21	*
Noise (Outdoor)	Cooling		45	45	50	49
Airflow Rate (High)	Indoor / Outdoor	m ³ /h	690/1720	690/1720	690/1830	*
Net Dimension H x W x D	Indoor	mm	260X790X198	260X790X198	260X790X198	280X790X203
		kg(lbs)	7.5(16.5)	7.5(16.5)	7.5(16.5)	8.0(17.6)
	Outdoor	mm	540X660X290	540X660X290	540X660X290	540X790X290
		kg(lbs)	23(50.6)	23(50.6)	29(63.8)	35(77)
Piping Connections (Small / Large)	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7
Drain Pipe Diameter (Inner/Outer)	mm		16/29	16/29	16/29	16/29
Max Pipe Length (Chargeless)	m		20(15)	20(15)	20(15)	20(15)
Max Height Difference	m		15	15	15	15
Operation Range	Cooling	°CDB	-10~43	-10~43	-10~43	-10~43
	Heating		-15~24	-15~24	-15~24	-15~24
Refrigerant			R410A	R410A	R410A	R410A

*: Data were not available at time of publication.


Powerful operation

20 minutes continuous operation by maximum airflow and maximum compressor speed is possible. Rapid cooling and heating makes the room comfortable quickly.



10°C HEAT Operation *Only available with Wireless RC.

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied




Caution

- When the room temperature is higher than 10°C, "10°C HEAT" operation does not start. Operation starts and maintains the room temperature at 10°C for 48 hours when the temperature drops below 10°C.
- When "10°C HEAT" operation stops, the room set temperature quickly returns to the preset temperature.

Low noise mode for outdoor unit

Low noise mode of outdoor unit can be selected by wireless remote controller.



Easy maintenance

Removable & washable panel



Filter sign display


Indicates the filter cleaning period by lamp.

Quiet operation

Cooling mode (07/09/12 TYPE)

Fan speed Quiet	Noise level 21dB_(A)
---------------------------	--

Low ambient operation



Optional parts

- Wired Remote Controller: UTY-RNNYM
- Simple Remote Controller: UTY-RSNYM
- Communication Kit: UTY-XCBXE (07/09/12 Type)
UTY-XCBXZ1 (14 Type)
- External Connect Kit: UTY-XWZX

Dimensions Models: ASYG07LE / ASYG09LE / ASYG12LE / ASYG14LE

(Unit : mm)

